			-
Your	ab TA name, and Lab Section day:	Yc	
	Tustin Fishbone		?
Co	rnell ENGRD 1170	Quiz 2	
	culators, books or notes allowed. utes total. No notes. No calculators. No text mess	Dec 3, 2009 aging.	
Dir	ections. To ease your TA's grading and t	o maximize your score, please:	
A+	Draw Free body diagrams whenever you use balance of forces or balance of moments.		
	TIDILY REDUCE and box in your answers (Don't leave simplifiable algebraic expressions).		
>>	Make appropriate Matlab code clear and correct. You can use shortcut notation like " $\theta_7 = 18$ " instead of, say, "theta7= 18". Small syntax errors will have small penalties.		
ightharpoons	Clearly define any needed dimensions $(\ell, h, d,)$ , coordinates $(x, y, r, \theta,)$ , variables $(v, m, t,)$ , base vectors $(\hat{i}, \hat{j}, \hat{e}_r, \hat{e}_\theta, \hat{\lambda}, \hat{n},)$ and signs $(\pm)$ with sketches, equations or words.		
<u>→</u>	Justify your results so a grader can distinguish an informed answer from a guess.		
3	If a problem seems powerly defined, clearly state any reasonable assumptions (that do not oversimplify the		

- Put your answer is in terms of well defined variables even if you have not substituted in the numerical

- Provide Matlab code which would generate the desired answer (and explain the nature of the output).

Work for **partial credit** (from 60-100%, depending on the problem)

- Reduce the problem to a clearly defined set of equations to solve.

Put your name on each extra sheet, fold it in, and refer to it at the relevant problem. Note the last page is blank for your use. Ask for more extra paper if you need it.

problem).

values.

1a) A car with mass m has motor, gears and wheels such that the forward force the wheels can supply is

$$F_{\boldsymbol{w}} = F_0 - c'v$$

where  $F_0$  and c' are constants and v is the speed of the car. Also acting on the car is air drag following the law

$$F_d = \frac{1}{2} c_d \rho A v^2$$

where  $c_d$  is the drag coefficient of the car,  $\rho$  is the density of air and A is the frontal area of the car. Answer all of the following questions in terms of some or all of the constants given above.

1a) Just when the car starts what is its forward acceleration  $a_{start}$ ?  $\sum_{i} F = m \quad a_{start} \qquad q_{s} = (F_{o} - c'_{s}) \quad \text{and} \quad q_{s} = (F_{o} - c'_{s}) \quad \text{and}$ 

- FW = map
- **1b**) What is the top speed  $v_{top}$  the car can reach on level ground?




1c) As the car goes faster and faster, when its speed is v (for some  $v < v_{top}$ ) what is its acceleration a? (Answer in terms of the constants given as well as the speed v).

a = (Fo-C'V) - (\frac{1}{2} cop Av2)

1d) Make a plot of v vs t and of x vs t for the car given that it starts at x = 0 and v = 0. The plots don't need to be quantitatively accurate, but just need to have the right general shapes (curved the right way with well labeled asymptotes).





to 
$$a = \frac{dV}{dt} = 0$$
 at  $V + cop$ 

$$\begin{cases}
F_{W}-F_{J}=ma \\
a = (F_{0}-c'_{V})-(\frac{1}{2}cdPA_{1}^{2})
\end{cases}$$

$$F_{0} = f_{d}$$

$$F_{0} - c'v = \frac{1}{2}c_{d}\rho Av^{2}$$

$$F_{0} = \frac{1}{2}c_{d}\rho Av^{2} - c'v$$

....

-

F

2) a) Assume you could change nothing but the gear box in the car from the previous problem (e.g., same motor, same wheels, same total mass, same air, same shape car). If you picked just the right dissipation-free gear box, how fast could you make the top speed of the car? Answer in terms of some or all of m,  $F_0$ , c',  $\rho$ , A and  $c_d$ ?


Genit N= At

**b**) Why not just equip cars with such a gear and no others? That is, why isn't that particular gear box not the best for all purposes? Be as specific as you can be.

This particular gear box is best for speed Depending on the gear rection of the gears of the gears of the gears or torque so this particular gear box would only be best for a situation where maxtop-speed of a car is the goal.




3) Draw any 3 bar truss that you like. Apply any non-zero load that you like. Carefully calculate the tension in any bar that you like. Your problem and solution need to be so clear that your work can be quickly evaluated and graded. You may use numbers or symbols (your choice) to define lengths, angles and loads. Draw big and clear.



water, density of finger, volume of water in the glass, area of the bottom of the glass, etc). The reading on the scale will go up. (22)/01-4 after PF = density of Junger Pw - density of water Vw = Volume of water scale would increase because the frager
13 taking up space where the wester ance was.

4) A glass of water, not totally full, is on a scale. You slowly put a finger into the water without touching the glass. When you put your finger in the water does the reading on the scale go up (how much?), down (how much?) or stay the same. Your answer must include convincing reasoning. Define and variables you need (e.g., density of

5) Two parallel plates with areas A are separated a distance h from each other with a viscous fluid in between with viscosity  $\mu$ . The bottom plate is fixed and the top one is dragged in its plane with speed v. What is the force needed to drag the plate? Assume the plates are very small, that h is much smaller than that and that v is small (Kirby lecture).



6) Comment critically on any one point from Professor Zellman Warhaft's lecture about Engineering and society. Explain it clearly as if to someone who did not see the lecture (e.g., Prof. Ruina who did not see the lecture).

Answer the best you can in no more than 5 minutes.

7) Describe an experiment to measure the Young's modulus E of a given material. How would you load what shape of material? What would you measure? Write a formula for E in terms of the quantities you would measure. Draw clear sketches with all quantities clearly defined by the sketch or in words.

